



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Kiilto Pro Epoxy Tile grout B - T3257

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Hardener for adhesives. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

KIILTO OY

PL 250

FI-33101 Tampere - FINLAND

Phone: +358 207 710 100

productsafety@kiilto.com

www.kiilto.com

1.4 Emergency telephone number: +358 (0)9 471 977

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Skin Corr. 1B: Skin corrosion, Category 1B, H314

Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352: IF ON SKIN: Gently wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a poison center/doctor.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local regulation

2.3 Other hazards:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Acid-based mixture of inorganic substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 9046-10-0 EC: 618-561-0 Index: Non-applicable REACH: 01-2119557899-12-XXXX	Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- ⁽¹⁾ Self-classified		25 - <50 %
	Regulation 1272/2008	Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1C: H314 - Danger	
CAS: 61788-44-1 EC: 262-975-0 Index: Non-applicable REACH: 01-2119979575-18-XXXX	Phenol, styrenated ⁽¹⁾ Self-classified		10 - <25 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	
CAS: 25513-64-8 EC: 247-063-2 Index: Non-applicable REACH: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine ⁽¹⁾ Self-classified		5 - <10 %
	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1: H317 - Danger	
CAS: 2156592-58-2 EC: 701-068-0 Index: Non-applicable REACH: 01-2119473798-17-XXXX	Amines, C12-18-(even numbered) and C18-(unsaturated) alky ⁽¹⁾ Self-classified		5 - <10 %
	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Skin Corr. 1B: H314; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 90-72-2 EC: 202-013-9 Index: 603-069-00-0 REACH: 01-2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol ⁽¹⁾ Self-classified		3 - <5 %
	Regulation 1272/2008	Acute Tox. 4: H302; Skin Corr. 1C: H314 - Danger	
CAS: 99-87-6 EC: 202-796-7 Index: 601-094-00-1 REACH: 01-2119881770-31-XXXX	p-cymene ⁽¹⁾ Self-classified		0,2 - <1 %
	Regulation 1272/2008	Acute Tox. 3: H331; Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Repr. 2: H361 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	Acute	10
	Chronic	10

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	LD50 oral	1240 mg/kg (ATEi)	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification	Acute toxicity		Genus
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	LD50 oral	910 mg/kg (ATEi)	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	LD50 oral	1200 mg/kg (ATEi)	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
p-cymene CAS: 99-87-6 EC: 202-796-7	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	3 mg/L (4 h) (ATEi)	Rat

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 7: HANDLING AND STORAGE (continued)

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- CAS: 9046-10-0 EC: 618-561-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	10,58 mg/m ³	Non-applicable
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	21 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	74 mg/m ³	Non-applicable
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	1 mg/m ³	0,38 mg/m ³	1 mg/m ³
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,15 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,53 mg/m ³	Non-applicable
p-cymene CAS: 99-87-6 EC: 202-796-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,88 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	Oral	Non-applicable	Non-applicable	7,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	7,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	13,1 mg/m ³	Non-applicable
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	Oral	Non-applicable	Non-applicable	0,04 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,035 mg/m ³	Non-applicable
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Oral	Non-applicable	Non-applicable	0,075 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,075 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,13 mg/m ³	Non-applicable
p-cymene CAS: 99-87-6 EC: 202-796-7	Oral	Non-applicable	Non-applicable	0,125 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,125 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,22 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

PNEC:



Identification				
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- CAS: 9046-10-0 EC: 618-561-0	STP	7,5 mg/L	Fresh water	0,015 mg/L
	Soil	0,018 mg/kg	Marine water	0,014 mg/L
	Intermittent	0,15 mg/L	Sediment (Fresh water)	0,132 mg/kg
	Oral	0,00693 g/kg	Sediment (Marine water)	0,125 mg/kg
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	STP	36,2 mg/L	Fresh water	0,004 mg/L
	Soil	0,0473 mg/kg	Marine water	0,0004 mg/L
	Intermittent	0,046 mg/L	Sediment (Fresh water)	0,248 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0248 mg/kg
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	STP	72 mg/L	Fresh water	0,102 mg/L
	Soil	10 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,315 mg/L	Sediment (Fresh water)	0,622 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,062 mg/kg
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	STP	0,55 mg/L	Fresh water	0,00026 mg/L
	Soil	10 mg/kg	Marine water	0,000026 mg/L
	Intermittent	0,0016 mg/L	Sediment (Fresh water)	3,76 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,376 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	STP	0,2 mg/L	Fresh water	0,046 mg/L
	Soil	0,025 mg/kg	Marine water	0,005 mg/L
	Intermittent	0,46 mg/L	Sediment (Fresh water)	0,262 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,026 mg/kg
p-cymene CAS: 99-87-6 EC: 202-796-7	STP	10 mg/L	Fresh water	0,004 mg/L
	Soil	0,302 mg/kg	Marine water	0 mg/L
	Intermittent	0,037 mg/L	Sediment (Fresh water)	1,52 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,152 mg/kg

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	 CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile)	 CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

- CONTINUED ON NEXT PAGE -





Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	 CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Non-applicable

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Characteristic
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	100 - 360 °C
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	11220,18 Pa (11,22 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	Non-applicable *
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Inappreciable in water
Decomposition temperature:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	110 °C (Does not maintain combustion)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	255 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: Mixture based on inorganic substances.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- CAS: 9046-10-0 EC: 618-561-0	LD50 oral	2885,3 mg/kg	Rat
	LD50 dermal	2979,7 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	Acute toxicity		Genus
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	LD50 oral	1240 mg/kg (ATEi)	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	LD50 oral	910 mg/kg (ATEi)	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	LD50 oral	1200 mg/kg (ATEi)	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
p-cymene CAS: 99-87-6 EC: 202-796-7	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	12200 mg/kg	Rabbit
	LC50 inhalation	3 mg/L (4 h) (ATEi)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- CAS: 9046-10-0 EC: 618-561-0	LC50	772,14 mg/L (96 h)	N/A	Fish
	EC50	80 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	15 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	29,5 mg/L (72 h)	Scenedesmus subspicatus	Algae
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	LC50	4,21 mg/L (96 h)	Danio rerio	Fish
	EC50	0,98 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0,39 mg/L (72 h)	Desmodesmus subspicatus	Algae
p-cymene CAS: 99-87-6 EC: 202-796-7	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	NOEC	10,9 mg/L	Danio rerio	Fish
	NOEC	1,02 mg/L	Daphnia magna	Crustacean
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	NOEC	Non-applicable		
	NOEC	0,013 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Substance-specific information:

Identification	Degradability		Biodegradability	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- CAS: 9046-10-0 EC: 618-561-0	BOD5	Non-applicable	Concentration	17.6 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Phenol, styrenated CAS: 61788-44-1 EC: 262-975-0	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	7 %
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine CAS: 25513-64-8 EC: 247-063-2	BOD5	Non-applicable	Concentration	10 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	7 %
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	BOD5	Non-applicable	Concentration	13 mg/L
	COD	Non-applicable	Period	29 days
	BOD5/COD	Non-applicable	% Biodegradable	64 %
p-cymene CAS: 99-87-6 EC: 202-796-7	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- CAS: 9046-10-0 EC: 618-561-0	BCF	
	Pow Log	1.34
	Potential	
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	BCF	173
	Pow Log	4.33
	Potential	High
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	BCF	3
	Pow Log	0.77
	Potential	Low
p-cymene CAS: 99-87-6 EC: 202-796-7	BCF	286
	Pow Log	4.1
	Potential	High

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Amines, C12-18-(even numbered) and C18-(unsaturated) alky CAS: 2156592-58-2 EC: 701-068-0	Koc	Non-applicable	Henry	1E-2 Pa·m³/mol
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Koc	15130	Henry	9,312E-12 Pa·m³/mol
	Conclusion	Immobile	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No
p-cymene CAS: 99-87-6 EC: 202-796-7	Koc	5011.87	Henry	1114,58 Pa·m³/mol
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	2,835E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 14*	Acids	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- | | | |
|------|--|--|
| 14.1 | UN number or ID number: | UN2735 |
| 14.2 | UN proper shipping name: | AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-; Phenol, styrenated) |
| 14.3 | Transport hazard class(es): | 8 |
| | Labels: | 8 |
| 14.4 | Packing group: | II |
| 14.5 | Environmental hazards: | Yes |
| 14.6 | Special precautions for user | |
| | Special regulations: | 274 |
| | Tunnel restriction code: | E |
| | Physico-Chemical properties: | see section 9 |
| | Limited quantities: | 1 L |
| 14.7 | Maritime transport in bulk according to IMO instruments: | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN2735
- 14.2 UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-; Phenol, styrenated)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** II
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
Special regulations: 274
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Segregation group: SGG18
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- 14.1 UN number or ID number:** UN2735
- 14.2 UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-; Phenol, styrenated)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances

p-cymene (99-87-6)

Substances that contribute to the classification (SECTION 2):

- Removed substances

Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- (9046-10-0)

Phenol, styrenated (61788-44-1)

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine (25513-64-8)

Amines, C12-18-(even numbered) and C18-(unsaturated) alky (2156592-58-2)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements
- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Kiilto Pro Epoxy Tile grout B - T3257

SECTION 16: OTHER INFORMATION ** (continued)

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -